

X-303 6B21.60
S3 SRC ESD

HYPERCLEAN
LINE | X-3

SIZES 36 - 48

SOFT PADDING

To improve the fit and comfort.

ANTIBACTERIAL MICROFIBER

Innovative material made of polyester fibers, water resistant and highly durable. Allows natural breathing.

FLOAT

The high tenacity fabrics for zero perforation give strong flexibility and lightness.

ALUMINIUM TOE CAP

Lightweight toe cap able to resist against pressure up to 200 Joules. Rubber coating for extra protection and easy cleaning.

CARBON PRO

Best conductive foam for maximum performance with lighter and high impulse properties.



HARD STICKY PU

Strategically positioned in the areas of most wear, to increase durability.

CLEATS

Open cleats for a better fluid dispersion.

DOUBLE DENSITY PU SOLE

This sole blends two different PU densities, where the midsole is extremely soft and comfortable, while the hard PU outsole provides great grip and resistance to oil and abrasion.



ALUMINIUM TOE CAP



FLOAT INSOLE



RESISTANCE TO WATER ABSORPTION



ELETROSTATIC DISCHARGE

NORMS EN ISO 20345:2011

S3 - Closed heel area with the following characteristics:

- E** - Heel energy absorption
- A** - Antistatic footwear
- FO** - Resistance to fuel oil of the outsole
- P** - Penetration resistance sole
- WRU** - Water penetration resistant uppers

ADDITIONAL CHARACTERISTICS:

- SRC** - Slip resistance on ceramic + sodium lauryl sulfate and steel + glycerin
- ESD** - Electrostatic Discharge (EN 61340-5-1)

ADVANTAGES

- Light | Comfortable | Breathable | Versatile | Sporty Look |
- Excellent anti-slip characteristics | Water absorption resistant materials

WORKING ENVIRONMENT

- Food Industry | Hotel Industry | Restaurants | Cleaning Industry